

# Xerox® Integrated Copy/Print Server

# for the Xerox® D95A/D110/D125 Copier/Printer

With the state-of-the-art Xerox® Integrated Copy/Print Server, the Xerox® D95A/110/125 Copier/Printer delivers a portfolio of the industry's most innovative features and capabilities. You'll get a simple workflow with an easy-to-use touchscreen, FreeFlow® integration, excellent features and a small footprint.



- **Ease of use.** Straightforward graphic user interface is rich in easily accessible features with large 10.4-inch full-colour touchscreen.
- **Superior scanning.** Create text-searchable files at the device for easy retrieval compression technology reduces network load for fast transmission.
- **Remotely manage your device.** Xerox® CentreWare® Software IS Embedded Web Server automates installation, troubleshooting feature set-up and upgrading.
- Multiple Sets of Copies with Separators. Make multiple collated or uncollated sets separated by slip sheets for efficient distribution.
- **Security.** A large set of security features is packed into one compact device, including Secure Print, data encryption/overwrite capabilities and optional removable hard drives.
- Copy and Save/Print and Delete Modes. Select "copy and save" on the touchscreen and, as you copy, document images and settings are saved to a mailbox/folder on the internal server.
- **Thumbnail Preview.** See a thumbnail view of your copy/scan job right at the touchscreen.
- **Bates Stamping.** Built-in Bates Stamping feature generates copies with customised alpha-numeric descriptors on each page.
- Extensible Interface Platform®. This is a software platform that allows productivity enhancing solutions to be easily accessed right at the copier/printer's touchscreen interface. Learn more about our many solutions offerings by visiting www.xerox.com/software-solutions
- Exception page programming. Easy programming of your jobs right at your PC or MAC® print driver, for example, colour covers and inserts, tabs and Z-folds.

### Xerox® D95A/D110/D125 Copier/Printer

## Standard Integrated Copy/Print Server Specifications

#### **Hardware Specifications**

- 250 GB Hard Disk Drive, 2 GB RAM
- 10.4-inch colour, touchscreen flat-panel display
- Ethernet interface (10 MBTX/sec, 100 MBTX/sec and 1000MBTX/sec)

#### **Client Environments Supported**

- Windows XP SP1 and above (32-and 64-bit), Server 2003/2008 (32-and 64-bit), Vista (32-and 64-bit), Windows 7 (32-and 64-bit)
- Mac OS 10.4 and above
- Citrix
- Custom driver for Unix: AIX 5 v5.3, HP-UX® 11.0/11i v2
- Oracle Solaris® 8/9/10
- Linux® Fedora Core 1/5
- Red Hat® ES4, SUSE 10/11
- Citrix and WHQL certification\*

  \*Dependent on configuration, software version

#### File Format Support

- Adobe<sup>®</sup> PostScript<sup>®</sup> 3<sup>™</sup>
- PDF
- PCL® 5e and 6
- TIFF
- HP-GL, HP-GL2

#### Network Environments/ Protocols

- TCP/IP, SNMP, SMB, Novell<sup>®</sup> IPX, AppleTalk<sup>®</sup>, IPP
- Copy and Save to mailbox/folders
- Preview documents from mailbox before printing
- Mailbox backup and restore
- IPv6 compliant

#### **Print Features**

- Automatic two-sided
- Secure print
- Delay print
- Sample set
- Booklet creation
- Cover selection
- Paper selection by attribute
- N-up
- Watermarks
- Banner sheets
- Fit to new paper size
- Output tray selection
- Print from and Scan to USB

#### **Accounting**

- Auditron
- Xerox<sup>®</sup> Standard Accounting (copy, print, fax, scan)
- Enabling colour access control
- Optional Network Accounting Enablement Kit
- Job-Based Accounting

#### **PDLs and Data Formats**

- PDF, XPS®, PCL 6 emulation, HP-GL2 (direct submission), TIFF, JPEG
- Adobe<sup>®</sup> PostScript<sup>®</sup> 3<sup>™</sup>

#### Scan and Copy

- Robust Set of Scan/Copy Functions –
   Plus Scan to Email, Scan to Folder, to PC, to Mailbox (private and public)
- Options include FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbnail Preview, Copy and store files for easy retrieval and reprint
- Scan to and Print from USB

#### **Other Options**

- Media Card Reader
- Common Access Card Enablement Kit
- Xerox Extensible Interface Platform® Enabled
- Foreign Device Interface
- Mobile / Smartphone Printing

#### **Data Security**

- Standard Secure Print
- Authentication with LDAP/Kerberos/ SMB/CAC
- Password-protected PDF
- FIPS 140-2 encryption
- S/MIME Encrypted Email
- IPsec
- 802.1X
- SNMP v3.0
- Email over SSL
- Image Overwrite (3x or 1x, Immediate, Scheduled, On Demand)
- Hard Disk Data Encryption
- Audit Log
- Optional CAC
- IPv6 Ready
- 256-bit Encryption
- Common Criteria Certified

#### **Electrical Requirements**

- Print Engine:
  - 208 to 240 VAC, 60/50 Hz, 15/13 amp service
- KVA Rating: Max Power Consumption:2.8 to 3.1 KVA
- Optional Feeding/Finishing:
- Each module requires 100 to 240 VAC, 60/50 Hz power

#### **Dimensions**

Print Engine:

– Width: 711 mm

- Depth: 787 mm

- Height: 1,460.5 mm

- Weight: 275 kg

#### **Agency Approvals**

ENERGY STAR®, CSA,

Europe: CE, NEMKO, RoHS, WEEE compliance

